

便携式储能电源规格书
PRODUCT SPECIFICATION SHEET

		产品品类：便携式储能电源 Product Name: Portable Power Supply 产品型号 (Model Number) :T101 可选规格 (Optional Type) :				
						
		欧规 European	美规 American	日规 Japanese	万能规 Universal	
规格参数 Product Specifications		配件: Accessories				
内置电池 Built-in Battery	高能量密度锂离子电池 High Quality Lithium ion Batteries 155Wh (4200mAh/3.7V)					
充电规格 Input Charging	适配器: DC15V/2A Power adapter: DC15V/2A (DC35135)					
太阳能充电规格 Solar Panel Input	MPPT, 13V~22V/2.0A (最大) MPPT, 13V~22V/2.0A Max					
充电时长 Fully Charged Time	DC:7~8 小时 DC:7h~8h					
USB输出 USB Output	2 x USB 输出 5V/2.1A Max 2 x USB output 5V/2.1A Max	适配器 power adapter				
	1 x USB 输出 5~9V/2A(QC3.0) 1 x USB output 5~9V/2A(QC3.0)					
	1 x USB C 输出 5~9V/2A(QC3.0) 1 x USB C output 5~9V/2A(QC3.0)					
		装箱数 Container Loading				
DC直流输出 DC Output	输出 9~12.5V/10A(13.5A Max) DC output 9~12.5V/10A(13.5A Max) (DC5521)	数量 / 20 dry Quantity / 20 dry		1800pcs		
AC交流输出 AC Output	AC 修正波输出 1 x AC Modified SineWave Output	数量 / 40 dry Quantity / 40 dry		3852pcs		
AC 持续输出功率 AC Continous Ouput	100W	数量 / 40HC Quantity / 40HC		4280pcs		
AC 峰值输出功率 AC Max Output		T101 包装 Packing				
照明 Bulb Type	4W LED照明/SOS/爆闪 4w LED Long bright, SOS, burst flash7		产品 UNIT	内盒 GIFT BOX	外箱 EXP CARTON	
工作温度 Operation temperature	-10℃~40℃	长度 (MM) Length (mm)	186	310	533	
循环寿命 Lifecycle	>500 次 500 times	宽度 (MM) Width (MM)	107	170	323	
产品认证 Certification	CE, FCC, RoHS, PSE, MSDS, UN38.3,	高度 (MM) Height (MM)	180	250	528	
产品保护 MultiSafety Protections	a. 短路保护 b. 过流保护 c. 过压保护 d. 欠压保护 e. 过载保护 f. 过温保护 a. Short-circuit protection b. Over-current protection c. Over-voltage protection d. Low-voltage protection e. Over-load Protection f. Over-temperature protection	重量 (KG) Weight (KG)	1.6	2.4	15.5	
		每箱数量 Units per Export Carton	6			
		包装清单 Packing list				
		1 x 便携储能箱 1 x 充电器 1 x 车充 1 x 点烟器转接头 1 x 说明书	1 x Portable power supply 1 x power adapter 1 x Car Charger 1 x Cigarette Lighter 1 x User Manual			